



# Proximity Card Reader **RF10/20/TINY**

## Key Features

- Up to 4" (10cm) read range
- User format available
- Wiegand, RS232, ABA track II magstripe format available
- Metal door frames, mullion (RF10/ RFTINY), and wall mount (RF20)
- PSK, FSK, ASK modulation
- Epoxy potted
- 100% Weather Proof

## General

The STAR RF10/20 and RFTINY (compact size & modern design) and a new attractive 4" (10cm) read range Proximity Reader which can be used in various Industrial applications (Access Control, Factory Automation, etc.).

It is designed to mount on metal door frame (mullion) with several fascinating colors.

Any of OEM proprietary format is available and it supports Wiegand format as well as RS232, ABA Track II magstripe format, Addressable RS422 and TTL output. These communications will allow you various applications in many industries.

The electronics reader parts in epoxy potting will ensure you its successful operations even in harsh environments (vandal proof) and indoor / outdoor (100% weather proof).

The elegant looking reader case is designed to match any interior decoration of ultramodern buildings.

Two color LED of green and red, inside digital buzzer sound will guarantee you an accurate system operation.



## Specifications

Read	IDK50	2 inch(5cm)
Range	IDC170	4 inch(10cm)
	IDC80	4 inch(10cm)
Reading Time	30ms	
Input voltage / Current	DC5~12V, max. 180mA (@DC12V RS232 output)	
Output format	26 bit Wiegand, RS232 and ABA track II magstripe format	
External Buzzer control Input	Low active, DC0~5V, max. 50mA, Impedance 10K ohm	
External LED control Input	Low active, DC0~5V, max. 50mA, Impedance 10K ohm	
LED / Buzzer	2 color LED (red and green), Piezo Buzzer	
Operating Environment	-35° F~149° F (-35°C~+65°C)	
Color	Dark pearl gray	
Weight	RF10 20	160g(0.35 lbs), 185g(0.41lbs)
	RFTINY	80g(0.18 lbs)
Dimensions	RF10	46 × 122 × 23mm
	RF20	76 × 124 × 23.5mm
	RFTINY	45 × 85 × 15.5mm

## Dimensions

